

Illuminated pushbutton 9.1 mm, with integrated filament lamp, momentary contact function, 1 NC + 1 NO, bezel yellow



fields of application

- Mechanical and system engineering
- Model construction
- Home technology

description

Mounting hole diameter 9.1 mm, max. 24 V / 500 mA, with integrated LED / filament lamp

technical data

➤ general

illuminated	Yes
Bezel color	yellow
Collar shape	round
Operating temperature, min.	-25 °C
Operating temperature, max.	55 °C
Storage temperature, min.	-40 °C
Storage temperature, max.	80 °C
Luminous elements	Filament lamp
Soldering time for manual soldering, max.	3 sec
Soldering temperature for manual soldering	350 °C
Soldering	Manual soldering
Packaging	Box
Packaging unit	10 pcs.
net weight	2.3 g
Operating life	200,000 Cycles
Degree of protection, front side, according to DIN EN 60529	IP40
RoHS compliant	Yes
REACH compliant	Yes
SAP MOQ order	10

➤ mounting diameters

Mounting hole	9.1 mm
Mounting depth	25 mm
Installation height	7 mm

direct links

- [RAFI eCatalog](#)

Outside dimension, width 11 mm

➤ **mechanical data**

Actuation function momentary contact function

Operating force, min. 5 N

Operating travel, max. 1.5 mm

Contact function 1 NC + 1 NO

Contact system Bridge contact

Contact material Gold

Fixing Threaded ring

Terminal on the rear Solder terminal

Lötbarkeit Yes

➤ **electrical data**

Operating voltage of the luminous element, max. 24 V

Operating current of the luminous element, max. 3 mA

Rated voltage, max. 24 V

Rated current, max. 0.5 A