

Bit Professional



|       |         |    |
|-------|---------|----|
| 38718 | 2 x T40 | 10 |
|       | 1 x T10 |    |
| 07874 | 1 x T15 | 10 |
|       | 1 x T20 |    |
|       | 1 x T20 |    |
| 32807 | 1 x T25 | 10 |
|       | 1 x T30 |    |
|       | 1 x T25 |    |
| 07875 | 1 x T30 | 10 |
|       | 1 x T40 |    |

| Order-No. |            |    |
|-----------|------------|----|
|           | 1 x 3,0    |    |
| 08419     | 1 x 3,5    | 10 |
|           | 1 x 4,0    |    |
|           | 1 x 5,5    |    |
| 08420     | 1 x 6,5    | 10 |
|           | 1 x 8,0    |    |
| 38676     | 2 x PH1    | 10 |
| 38706     | 2 x PH1    | 10 |
| 36193     | 2 x PH2    | 10 |
| 38707     | 2 x PH2    | 10 |
| 38677     | 2 x PH3    | 10 |
| 38708     | 2 x PH3    | 10 |
| 38679     | 2 x PZ1    | 10 |
| 38709     | 2 x PZ1    | 10 |
| 38680     | 2 x PZ2    | 10 |
| 38710     | 2 x PZ2    | 10 |
| 38681     | 2 x PZ3    | 10 |
| 38711     | 2 x PZ3    | 10 |
| 36086     | 2 x SL/PZ1 | 10 |
| 36082     | 2 x SL/PZ2 | 10 |
| 32805     | 1 x T20    | 10 |
| 32806     | 1 x T25    | 10 |
| 38684     | 2 x T10    | 10 |
| 38712     | 2 x T10    | 10 |
| 38685     | 2 x T15    | 10 |
| 38713     | 2 x T15    | 10 |
| 38686     | 2 x T20    | 10 |
| 32808     | 1 x T20    | 10 |
| 38714     | 2 x T20    | 10 |
| 38687     | 2 x T25    | 10 |
| 32809     | 1 x T25    | 10 |
| 38715     | 2 x T25    | 10 |
| 38688     | 2 x T27    | 10 |
| 38716     | 2 x T27    | 10 |
| 38689     | 2 x T30    | 10 |
| 38717     | 2 x T30    | 10 |
| 38690     | 2 x T40    | 10 |

Bit set Professional 70 mm



TORX® ball end 1/4" in bit band 10-pcs.

7045BE 9570

| Order-No. |   |   |
|-----------|---|---|
| 32804     |   | 1 |
|           | 2 x T10 / 2 x T15 / 2 x T20 / 2 x T25 / 2 x T30 |   |

INFOBOX:  
TORX® ball end



Wiha TORX® ball end

- With optimised TORX® ball end geometry
- Increased strength thanks to the special cold forming on a system developed by Wiha especially for this purpose.
- Allows fastening and unfastening at angles up to 25°.
- Simple insertion of the tool/bit and fastening/unfastening, especially in hard-to-reach positions.
- Broad product range: As an L-key, as a bit and as a SoftFinish® screwdriver.