

TorqueFix®-Key.



NEW

2836

TorqueFix® key torque screwdriver.**With a fixed torque value pre-set by Wiha.****Automatic release.**

Handle: Ergonomic key handle, extremely handy thanks to its compact design. Specially for hard-to-reach screws and confined spaces.

Audible and perceptible click when the pre-set torque has been attained.

Compatible with all blades of the 2859 series.

Standards: EN ISO 6798, BS EN 26789, ASME B107.14M.

Accuracy: ±6%, traceable to national standards.

Application: For applications where recommended torque settings are important. Loosening torque approx. +30% greater than tightening torque.

Extra: Delivered in practical plastic box.

Incl. factory calibration certificate.

Note: Further articles can be individualised and set at mytorque.wiha.com or on request.

Order-No.	Nm	±%	⌀	↔	↔	↔
38616	0.5	6%	4	68	50	1
38617	0.6	6%	4	68	50	1
38618	0.9	6%	4	68	50	1
38556	1.1	6%	4	68	50	1
38800	1.2	6%	4	68	50	1
38619	1.4	6%	4	68	50	1
38557	2.0	6%	4	68	50	1
38620	2.5	6%	4	68	50	1
38621	3.0	6%	4	68	50	1
38558	3.8	6%	4	68	50	1
38622	4.0	6%	4	68	50	1

Torque interchangeable blades.



NEW

28369

Torque hex interchangeable blade.**For Wiha TorqueFix® key torque screwdrivers.**

Blade: High-quality chrome-vanadium molybdenum steel, through-hardened, titanium silver.

Application: For applications where recommended torque settings are important.

Extra: Very slim blade diameter for hard-to-reach screws.

Order-No.	⌀	⌀	↔	↔	max. Nm	↔
38801	1.5	4	75	20	0.9	10
38802	2.0	4	75	20	1.8	10
38803	2.5	4	75	20	3.8	10
38804	3.0	4	75	20	5.5	10
38805	4.0	4	75	20	8.0	10



NEW

28369

Torque TORX® interchangeable blade.**For Wiha TorqueFix® key torque screwdrivers.**

Blade: High-quality chrome-vanadium molybdenum steel, through-hardened, titanium silver.

Application: For applications where recommended torque settings are important.

Extra: Very slim blade diameter for hard-to-reach screws.

Order-No.	⌀	⌀	↔	↔	max. Nm	↔
38806	T6	4	75	20	0.6	10
38807	T7	4	75	20	0.9	10
38808	T8	4	75	20	1.3	10
38809	T9	4	75	20	2.5	10
38810	T10	4	75	20	3.8	10
38811	T15	4	75	20	5.5	10
38812	T20	4	75	20	8.0	10
38813	T25	4	75	20	8.0	10



NEW

28369

Torque TORX PLUS® interchangeable blade.**For Wiha TorqueFix® key torque screwdrivers.**

Blade: High-quality chrome-vanadium molybdenum steel, through-hardened, titanium silver.

Application: For applications where recommended torque settings are important.

Extra: Very slim blade diameter for hard-to-reach screws.

Order-No.	⌀	⌀	↔	↔	max. Nm	↔
38814	6IP	4	75	20	0.8	10
38815	7IP	4	75	20	1.3	10
38816	8IP	4	75	20	2.0	10
38817	9IP	4	75	20	3.0	10
38818	10IP	4	75	20	4.5	10
38819	15IP	4	75	20	6.6	10
38820	20IP	4	75	20	8.0	10
38821	25IP	4	75	20	8.0	10