



Main

| | |
|------------------------------|-------------------------|
| Device short name | MN |
| Product or component type | Voltage release |
| Device application | Control |
| Range compatibility | EasyPact EZC |
| Voltage release type | Undervoltage release |
| [Uc] control circuit voltage | 200...240 V AC 50/60 Hz |

Complementary

| | |
|----------------------------|--|
| Threshold tripping voltage | 0.35...0.7 Un opening 0.85 Un closing |
| Response time | 50 ms |

Packing Units

| | |
|------------------|----------|
| Package 1 Weight | 0.045 Kg |
| Package 1 Height | 0.250 Dm |
| Package 1 width | 0.700 Dm |
| Package 1 Length | 0.850 Dm |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH free of SVHC | Yes |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS Declaration |
| Environmental Disclosure | Product Environmental Profile |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

| | |
|-----------------------|----------------|
| Product Life Status : | Commercialised |
|-----------------------|----------------|